

Conventional Fire Alarm Panel GST101



Features and Benefits

1. Microprocessor controlled SMT Electronics
2. Compliant with EN54 part 2&4, & BS5839, Part 4, 1988
3. Both end of line resistors and active end of line can be used.
4. Programmable sounder circuits and outputs
5. Fully monitored sounder circuits
6. Key control evacuate over-ride
7. Class change terminals for remote control
8. Up to 25 fire detectors and infinite manuals call points zone capacity

Description

GST101 Conventional Fire Panel is a kind of multi-wire fire panel using single-chip microprocessor. It can detect 1 zone. Each zone can at most be connected with 15 conventional detectors. It has 2 output control points through which it can control some indicators, such as sounder strobes and sounders, etc. The panel is designed with stand-by batteries (two sealed acid storage batteries) and reserved space for installation; It has functions of operation indication, fault indication, alarm indication and cable checking for short circuit or broken circuit. It can also identify the location of detecting zone. Installation and operation of the panel are very simple. All control functions are realized through a key switch.

Technical Specifications

- Approvals: LPCB
- Operating Voltage
DC24V±15% or AC220V 50Hz
- Stand-by batteries are configured on order. The battery capacity can be calculated according to the formula in Clause 5.6 of this manual. The maximum capacity is 4Ah (lasting for 24 hours in monitoring state).
- Output voltage: DC20V DC28V
- Static current: 2.4mA (connected with 15 conventional detectors)
- Resistance when alarming fire: 150Ω 1.5kΩ (normally 470Ω)
- Terminal resistor: 4.7kΩ or using active end of line unit(.AEOL)
- Sounder: Output voltage DC20V to DC28V, output current 1A, terminal resistor 4.7kΩ.
- Fault: Passive contact output, capacity 1A DC24V
- Dimension: 210mm×297mm×90mm

Selection of compatible devices.

Compatible with all GST conventional detectors and sounders.

Ordering Information:

Part No	Description	Weight /Kg	Pack Qty per Box
GST101	1 Zone Conventional Fire Alarm Control Panel	2.45	1

MANUFACTURED IN ACCORDANCE WITH



Note: Specifications are subject to change without notice.

GST England Lion Court, Staunton Harold Hall, Melbourne Road, Ashby de la Zouch, Leicestershire, England LE65 1RT Tel: +44 1283 225 478 Fax: +44 1283 220 690

GST Dubai ZA04, Jebel Ali Free Zone, P.O.Box 17998, Dubai UAE
Tel: +971 (0)4 8833 050 Fax: +971 (0)4 8833 053

GST China 80, Changjiang East Road, Economic & Technology Development Zone Qinhuangdao, Hebei, China Tel: +86(0)335 850 2383 Fax: +86 (0)335 850 7588



www.gst.uk.com
info@gst.uk.com